

# **Cultivator Springs**

Cultivator springs are crucial components in agricultural machinery, designed to enhance the efficiency and durability of cultivators and tillers. Cultivator springs act as shock absorbers, mitigating the impact of rocks, roots, and other obstacles encountered during plowing. This helps prevent damage to the equipment and ensures smoother operation. They provide flexibility to the tines or blades of the cultivator, allowing them to move over uneven terrain without breaking or bending.

Product code	Spring Type (COILS x OD)	Weight	Wire dia Ø
		KG	ММ
SPR-9.2-2646	26×46	1.55	9.2
SPR-9.2-2648	26×48	1.66	9.2
SPR-9.2-2650	26×50	1.75	9.2
SPR-9.2-2746	27×46	1.60	9.2
SPR-9.2-2748	27×48	1.67	9.2
SPR-9.2-2750	27×50	1.80	9.2
SPR-9.2-2846	28×46	1.66	9.2
SPR-9.2-2848	28×48	1.77	9.2
SPR-9.2-2850	28×50	1.88	9.2
SPR-9.2-29H46-M	29.5×46	1.76	9.2
SPR-9.2-29H48-M	29.5×48	1.86	9.2
SPR-9.2-29H50-M	29.5×50	2.00	9.2

### CULTIVATOR SPRING ( REGULAR WIRE 9.2 MM )

### CULTIVATOR SPRING (SPL. STEEL WIRE 9.5 SSL)

		,	
PRODUCT CODE	Spring Type (COILS x OD)	Weight	Wire Dia Ø
		KG	ММ
SPR-9.5-2648	26×48	1.75	9.5
SPR-9.5-2650	26×50	1.95	9.5
SPR-9.5-2748	27×48	1.80	9.5
SPR-9.5-2750	27×50	2.00	9.5
SPR-9.5-29H48-M	29.5×48	1.95	9.5
SPR-9.5-29H50-M	29.5×50	2.15	9.5



# CULTIVATOR SPRING (SPL. STEEL WIRE 10MM SSL)

PRODUCT CODE	Spring Type (C	COILS x OD ) Weight KG	Wire Dia Ø
		KG	ММ
SPR-10-2548	25×48	1.86	10
SPR-10-2550	25X50	2.04	10
SPR-10-2648	26×48 2.00	2.00	10
SPR-10-2650	26×50	2.12	10
SPR-10-29H48-M	28.5×48	2.20	10
SPR-10-29H50-M	28.5×50	2.33	10

# CULTIVATOR SPRING (SPL. STEEL WIRE 11MM SSL GRADE 2)

PRODUCT CODE	Spring Type (COILS x OD)	Weight KG	Wire Dia Ø
		KG	MM
SPR-11-2350	23×50	2.20	11
SPR-11-2352	23×52	2.30	11
SPR-11-23H50	23.5×50	2.25	11
SPR-11-23H52	23.5×52	2.35	11
SPR-11-2450	24X50	2.30	11
SPR-11-2452	24×52	2.40	11
SPR-11-2550	25X50	2.41	11
SPR-11-2552	25X52	2.50	11
SPR-11-2650-M	26X50	2.51	11
SPR-11-2652-M	26×52	2.60	11

#### CULTIVATOR SPRING (SPL. STEEL WIRE 12 SSL GRADE 2)

PRODUCT COD E	Spring Type	(COILS x OD)	Weight KG	Wire Dia Ø
			KG	ММ
SPR-12-2155	21	×55	2.70	12
SPR-12-2255	22	X 55	2.85	12
SPR-12-2355	23	X 55	3.00	12
SPR-12-24H55-M	24.5	X 55	3.15	12